

## 3" Tank Top Weld-in Flanges

316L flanges to be welded on top of tanks

Perolo 316L stainless steel weld-in flanges are to be welded on top of tank containers, IBC's, road tankers, rail tank cars and storage tanks in order to fit valves and accessories



### Specifications

- 316L stainless steel construction
- Nominal diameter 3"
- Drillings depending on application
- Radiused angles
- Serrated gasket contact area

### Options


- Other diameter weld-in flanges
- Other materials (Aluminum, 304L, 904L...)
- Other drilling

| 11 90 36 00 00  |                          |
|-----------------|--------------------------|
|                 | <b>External diameter</b> |
|                 | 200mm                    |
|                 | <b>Internal diameter</b> |
|                 | 94mm                     |
|                 | <b>Thickness</b>         |
| 26.5mm          |                          |
| <b>Drilling</b> |                          |
| 6xM12xPCD168mm  |                          |
| 4xM16xPCD160mm  |                          |

| 11 90 37 00 00   | DN80 PN10 & 3"ASA150     |
|------------------|--------------------------|
|                  | <b>External diameter</b> |
|                  | 200mm                    |
|                  | <b>Internal diameter</b> |
|                  | 94mm                     |
|                  | <b>Thickness</b>         |
| 26.5mm           |                          |
| <b>Drilling</b>  |                          |
| 8xM16xPCD160mm   |                          |
| 4xM16xPCD152.4mm |                          |

| 12 91 61 10 00  |                          |
|-----------------|--------------------------|
|                 | <b>External diameter</b> |
|                 | 200mm                    |
|                 | <b>Internal diameter</b> |
|                 | 94mm                     |
|                 | <b>Thickness</b>         |
| 26.5mm          |                          |
| <b>Drilling</b> |                          |
| 6xM12xPCD168mm  |                          |

| 11 91 98 00 00  | DN80 PN10                |
|-----------------|--------------------------|
|                 | <b>External diameter</b> |
|                 | 200mm                    |
|                 | <b>Internal diameter</b> |
|                 | 94mm                     |
|                 | <b>Thickness</b>         |
| 26.5mm          |                          |
| <b>Drilling</b> |                          |
| 6xM12xPCD168mm  |                          |
| 8xM16xPCD160mm  |                          |



## 3" Tank Top Weld-in Flanges

316L flanges to be welded on top of tanks

| 11 92 56 00 00  | Siphon tube provision<br>DN50 PN10                 |
|-----------------|--|
|                 | <b>External diameter</b>                           |
|                 | 200mm  |
|                 | <b>Internal diameter</b>                           |
|                 | 94mm   |
|                 | <b>Thickness</b>                                   |
| 26.5mm          |  |
| <b>Drilling</b> | 6xM12xPCD168mm<br>4xM16xPCD160mm<br>4xM16xPCD125mm |

| 17 12 16 00 01  | Siphon tube provision            |
|-----------------|----------------------------------|
|                 | <b>External diameter</b>         |
|                 | 200mm                            |
|                 | <b>Internal diameter</b>         |
|                 | 94mm                             |
|                 | <b>Thickness</b>                 |
| 26.5mm          |                                  |
| <b>Drilling</b> | 6xM12xPCD168mm<br>4xM16xPCD160mm |

| 12 92 08 00 01  | Siphon tube provision    |
|-----------------|--------------------------|
|                 | <b>External diameter</b> |
|                 | 200mm                    |
|                 | <b>Internal diameter</b> |
|                 | 95mm                     |
|                 | <b>Thickness</b>         |
| 26.5mm          |                          |
| <b>Drilling</b> | 6xM12xPCD168mm           |

| 11 91 87 00 00  | Siphon tube provision            |
|-----------------|----------------------------------|
|                 | <b>External diameter</b>         |
|                 | 200mm                            |
|                 | <b>Internal diameter</b>         |
|                 | 95mm                             |
|                 | <b>Thickness</b>                 |
| 26.5mm          |                                  |
| <b>Drilling</b> | 6xM12xPCD168mm<br>4xM16xPCD160mm |

| 11 90 98 00 00         | Recessed                         |
|------------------------|----------------------------------|
|                        | <b>External diameter</b>         |
|                        | 217mm                            |
|                        | <b>Internal diameter</b>         |
|                        | 94mm                             |
|                        | <b>Thickness</b>                 |
| Min : 31mm; Max : 56mm |                                  |
| <b>Drilling</b>        | 6xM12xPCD168mm<br>4xM16xPCD160mm |

| 11 90 76 00 00         | Recessed<br>Siphon tube provision |
|------------------------|-----------------------------------|
|                        | <b>External diameter</b>          |
|                        | 217mm                             |
|                        | <b>Internal diameter</b>          |
|                        | 94mm                              |
|                        | <b>Thickness</b>                  |
| Min : 31mm; Max : 56mm |                                   |
| <b>Drilling</b>        | 6xM12xPCD168mm<br>4xM16xPCD160mm  |

| 11 90 99 00 00         | Recessed<br>DN80 PN10 – 3"ASA 150  |
|------------------------|------------------------------------|
|                        | <b>External diameter</b>           |
|                        | 217mm                              |
|                        | <b>Internal diameter</b>           |
|                        | 94mm                               |
|                        | <b>Thickness</b>                   |
| Min : 31mm; Max : 56mm |                                    |
| <b>Drilling</b>        | 4xM16xPCD152.4mm<br>8xM16xPCD160mm |

| 11 93 32 00 00         | Recessed                         |
|------------------------|----------------------------------|
|                        | <b>External diameter</b>         |
|                        | 217mm                            |
|                        | <b>Internal diameter</b>         |
|                        | 94mm                             |
|                        | <b>Thickness</b>                 |
| Min : 31mm; Max : 56mm |                                  |
| <b>Drilling</b>        | 6xM12xPCD168mm<br>8xM16xPCD160mm |