



Adaptor flanges 316L adaptor flanges

Perolo 316L stainless adaptor flanges are designed to be placed in between weld-in flanges and fittings for tank containers, IBC's, road tankers, rail tank cars and storage tanks.



Specifications

- 316L stainless steel construction
- Drillings depending on application
- Radiused angles
- Serrated gasket contact area

Options

- Other diameter flanges
- Other materials (Aluminum, 304L, 904L...)
- Other drilling

11 91 15 00 00	Pressure gauge Protection & ¼" BSP connection
	External diameter 127mm
	Internal diameter 2 ½" BSP threaded
	Thickness 22.5mm
	Drilling 6x11xPCD105mm

11 91 15 00 01	Pressure gauge ¼" BSP connection
	External diameter 127mm
	Internal diameter 2 ½" BSP threaded
	Thickness 22.5mm
	Drilling 6x11xPCD105mm

11 93 59 00 00	2 ½" – 3" with pressure gauge, gauge protection & ¼" BSP connection
	External diameter 183mm
	Internal diameter 2 ½" BSP threaded
	Thickness 25mm
	Drilling 4x18xPCD150mm

11 93 88 00 00	2 ½" – 3" With ¼" BSP connection
	External diameter 165mm
	Internal diameter 2 ½" BSP threaded
	Thickness 21mm
	Drilling 4x18xPCD130mm



Adaptor flanges

316L adaptor flanges

11 12 67 20 00	2" Siphon tube guide ring
	External diameter
	104.5mm
	Tube diameters
	Int. Ø 52mm, Ext Ø 60mm
	Thickness
17mm	
Tube length	46mm

12 92 18 10 00	3" Siphon tube guide
	External diameter
	200mm
	Tube diameters
	Int. Ø 80mm, Ext Ø 93mm
	Thickness
8mm	
Drilling	4x18xPCD160mm 6x14xPCD168mm

11 93 82 00 00	
	External diameter
	200mm
	Tube diameters
	Int. Ø 80mm, Ext Ø 93mm
	Thickness
10mm	
Drilling	8x18xPCD160mm

11 92 86 00 00	2" - 3"
	External diameter
	200mm
	Internal diameter
	50mm
	Thickness
21mm	
Drilling	4xM16xPCD125mm 4x18xPCD160mm

11 91 62 00 00	
	External diameter
	200mm
	Internal diameter
	90mm
	Thickness
20mm	
Drilling	4x18xPCD160mm 4xM16xPCD160mm

12 91 41 00 03	for Tankfly DN80
	External diameter
	200mm
	Internal diameter
	90mm
	Thickness
24mm	
Drilling	4x18xPCD160mm 4xM16xPCD160mm

11 92 95 00 00	
	External diameter
	200mm
	Internal diameter
	62mm
	Thickness
19mm	
Drilling	4xM16xPCD125mm 4x18xPCD160mm

11 91 79 00 00	
	External diameter
	200mm
	Internal diameter
	50mm
	Thickness
28mm	
Drilling	4xM16xPCD125mm 4x18xPCD160mm