


## Blind Flanges

316L blind flanges – Page 1/2

Perolo 316L stainless steel blind flanges are designed to close valves or flanges welded on tank containers, IBC's, road tankers, rail tank cars and storage tanks.



### Specifications

- 316L stainless steel construction
- Drillings depending on application
- Radiused angles
- Serrated gasket contact area

### Options

- Other diameter blind flanges
- Other materials (Aluminum, 304L, 904L...)
- HALAR® coating for corrosive products

11 90 01 00 00	
	<b>External diameter</b>
	127mm
	<b>Thickness</b>
	8.5mm
	<b>Drilling</b>
	6x11xPCD105mm


11 92 57 00 00	
	<b>External diameter</b>
	127mm
	<b>Thickness</b>
	8.5mm
	<b>Drilling</b>
	4x12xPCD103.5mm

11 92 99 00 00	ND40 PN10
	<b>External diameter</b>
	150mm
	<b>Thickness</b>
	8.5mm
	<b>Drilling</b>
	4x18xPCD110mm

17 12 12 16 01	ND50 PN10
	<b>External diameter</b>
	165mm
	<b>Thickness</b>
	8.5mm
	<b>Drilling</b>
	4x18xPCD125mm

11 90 48 00 00	ND65 PN10
	<b>External diameter</b>
	190mm
	<b>Thickness</b>
	8.5mm
	<b>Drilling</b>
	4x18xPCD145mm

12 85 49 00 01	
	<b>External diameter</b>
	200mm
	<b>Thickness</b>
	8.5mm
	<b>Drilling</b>
	4x18xPCD160mm



# Blind Flanges

316L blind flanges – Page 2/2

<b>11 92 09 00 00</b> 	<b>To welcome A pivot pin assembly</b>
	<b>External diameter</b> 200mm
	<b>Thickness</b> 8.5mm
	<b>Drilling</b> 4x18xPCD160mm

<b>11 90 13 00 00</b> 	<b>External diameter</b> 200mm
	<b>Thickness</b> 8.5mm
	<b>Drilling</b> 6x14xPCD168mm

<b>11 90 41 00 00</b> 	<b>Dished</b>
	<b>External diameter</b> 200mm
	<b>Thickness</b> 8.5mm
	<b>Drilling</b> 4x18xPCD160mm

<b>11 93 09 00 00</b> 	<b>Slotted holes</b>
	<b>External diameter</b> 200mm
	<b>Thickness</b> 8.5mm
	<b>Drilling</b> 4x18xPCD145.5-160mm