









2" TANKFLY™ Flanged


Series TF4X butterfly valves


The 2" TANKFLY™ flanged butterfly valve is designed to be used as an air inlet/outlet valve.

Made of 316L/1.4404 stainless steel, the TANKFLY™ valve is applicable to tank containers, rail tanks, road tankers and static tanks dedicated to transporting or storing chemicals and liquid foodstuff.



Specifications





Nominal diameter: 51mm (2")Maximum weight: 4 kg

• Container side flange: 4 x Ø18 on a Ø125PCD

• Outlet side flange: 4 x slots 18 on a min Ø114PCD

• MAWP : 4 bar • Test pressure : 6 bar • Design Temperature : 190°C

• Working Temperature : -40°C +150°C

Approval & Certifications

- Comply with IMDG & ADR
- Comply with EN14432
- Approved by Bureau Veritas

Features

- Full 316L/1.4404 stainless steel construction
- · Compact design. Face to face : 66mm
- 1/4 turn operation
- · Easy filter change
- FEP/PTFE seals
- Pressure gauge connection

Options

- Extreme resistance to corrosion with :
- HALAR coating body
- Closure plate & closure seal in Hastelloy C276
- Over pressure valve connection
- Sintered disc
- Gauge protection

Accessories

Filter.
Weld in flange.
Recess flange.
Bolting kit.
Gasket.
Blind flange.
Tool kit for sleeve installation.
Part#11 12 03 94 00
Part#11 90 25 00 00
Part#11 92 44 00 00
Part#11 91 13 91 00
Part#11 90 29 00 00
Part#17 12 12 16 01
Part#11 12 03 98 00










2" TANKFLY™ Flanged

Series TF4X butterfly valves

Codification



For any specific requests, please feel free to contact our sales department at sales@perolo.com



